

TRADITIONAL RACE FUELS

SUNOCO® HCR PLUS™

An ultra high performance leaded racing fuel designed for racing engines with very high compression ratios. HCR Plus™ is ideally suited for applications in sustained high load/high rpm conditions. This fuel contains no oxygenates and is very resistant to vapor lock. Sunoco HCR Plus is recommended for four-stroke engines with compression ratios exceeding 14:1.

The logo for HCR Plus features the letters 'HCR' in a large, bold, yellow font with a black outline. Below 'HCR', the word 'Plus' is written in a smaller, yellow, cursive font. A yellow brushstroke underline is positioned beneath the 'HCR' text.

1-800-RACE-GAS
www.racegas.com

FUEL PROPERTY	TYPICAL SPECIFICATIONS
Specific Gravity	0.739
Antiknock Index (R+M)/2	114
RON, Research Octane	118
MON, Motor Octane	110
Reid Vapor Pressure	6.0
Distillation, °F	
Initial Boiling Point	102
10% Evaporation	181
50% Evaporation	217
90% Evaporation	226
Final Boiling Point	245
Leaded	Yes For Off-Road Use Only
Color	Orange
Oxygen, Wt%	0.0%
Dielectric Constant	0.6

**BECAUSE QUALITY AND
CONSISTENCY COUNT!**