

## TRADITIONAL RACE FUELS

# SUNOCO® MAXNOS™

Sunoco® MaxNOS™ is a leaded racing fuel designed for engines incorporating maximum cylinder pressure. It is particularly beneficial in nitrous, supercharged, and turbocharged applications. MaxNOS has superseded Sunoco Supreme NOS and has proven to be even more robust and better suited to extreme combustion environments. Sunoco MaxNOS is for off-road and racing use only. MaxNOS contains additives to enhance stability and minimize oxidative effects. As with any gasoline, it should be stored in dark, tightly sealed containers where the temperature is stable.



1-800-RACE-GAS  
www.racegas.com

FUEL PROPERTY	TYPICAL SPECIFICATIONS
Specific Gravity	0.733
Antiknock Index (R+M)/2	116
RON, Research Octane	119
MON, Motor Octane	113
Reid Vapor Pressure	5.7
Distillation, °F	
Initial Boiling Point	104
10% Evaporation	181
50% Evaporation	217
90% Evaporation	227
Final Boiling Point	247
Leaded	Yes <i>For Off-Road Use Only</i>
Color	Yellow
Oxygen, Wt%	0.0%
Dielectric Constant	0.2

**BECAUSE QUALITY AND CONSISTENCY COUNT!**